

EDGE[®]

INDUSTRIAL WORK GLOVES

82-133

Disposable Nitrile Gloves



Nitrile



Multi-Purpose

Affordable protection and comfort

Features and Benefits

- Manufactured with a thinner nitrile formulation that increases comfort and improves flexibility without compromising protection.
- Offers textured fingertips to provide an improved grip for a variety of applications.
- Packed 300 gloves per dispenser box to provide additional value and convenience.
*250 pieces/dispenser for size XL.

Industries

- Automotive
- Chemical (Basic, Specialty & Petrochemical)
- Food Processing & Services
- Janitorial
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices)
- Manufacturing (Appliances, Raw Materials, etc.)
- Recycling & Waste Disposal

Applications

- Compounding, mixing, blending
- Fastening, screwing, unscrewing parts
- Food processing and handling
- Catering
- Handling compression press and tablet manufacturing
- Handling of machined parts coated with light oil
- Handling of paint/glue guns & sprayers
- Inspection and tooling precision maintenance
- Lab work, blending, compounding, filling, cleaning
- Maintenance and equipment clean up



EDGE[®]

INDUSTRIAL WORK GLOVES

82-133

Disposable Nitrile Gloves

TECHNICAL DATA:

PRODUCT INFORMATION:

	82-133
Material	Nitrile
Colour	Cobalt Blue
Glove Design	Ambidextrous, Powder free, Textured fingers, Light Weight Product
Cuff	Beaded
Audit Standards	ISO 9001
Quality Control	Compliant with ASTM D 3577, Type II
Packaging	300 gloves per dispensers, 10 dispensers per shipper, 3000 gloves per shipper* *Size XL 250 pieces/dispenser, 2500 pieces/shipper
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	PROPERTY	TYPICAL VALUES					TESTING METHOD
	SIZE	XS 5½-6	S 6½-7	M 7½-8	L 8½-9	XL 9½-10	ASTM D3767 / EN 420
Length (mm)	82-133	230	230	230	230	230	
Average Palm Width (mm)	82-133	70	80	95	110	120	

Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D6319-10 ASTM D5151-06 (2011)
Palm Thickness Single Wall	0.06 mm (2.5 mil)					ASTM D3767 / EN 420
	BEFORE AGING			AFTER AGING		
Ultimate Tensile Strength	> 14 Mpa Typical value 14-20			> 14 Mpa Typical value 14-18		ASTM D6319-10
Elongation at Break (%)	> 500 Typical value 500-600			> 400 Typical value 400-550		ASTM D6319-10

ORDERING INFORMATION:

	SIZE	XS Size 5½-6	S Size 6½-7	M Size 7½-8	L Size 8½-9	XL Size 9½-10
82-133	REORDER #	82133060	82133070	82133080	82133090	82133100

Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application. Ansell is not responsible for damage resulting from inappropriate use, fair wear and tear, defective or careless handling or use of inappropriate operating means.

For additional information visit us at www.ansell.com, or call us at
North America, Latin America and Caribbean: +1800 800 0444
Asia Pacific: +852 2185 0600
Europe: +32 2 528 74 00
Australia: +61 3 9270 7270

® and ™ are trademarks owned by Ansell Limited or one of its affiliates.
© 2015 Ansell Limited. All Rights Reserved.



ERC
TP TC 019/2011



CE 0493

Ansell
Protects™