

▲ INTEGRA® & INTEGRA® EC

BLUE
NITRILE
NON-STERILE
AMBIDEXTROUS
FULLY TEXTURED
BEADED CUFF
FOR SINGLE USE ONLY

POWDER-FREE STANDARD & EXTENDED CUFF EXAMINATION GLOVES

Integra® is a durable 8 mil glove, perfect for tough jobs where extra durability or safety is needed. The added thickness of these gloves gives strength and durability. Great protection against bloodborne pathogens.

• Extra thickness for extra protection





INTEGRA® PRODUCT CODE					
S	N861				
М	N862				
L	N863				
XL	N864				
XXL	N865				

S	N8/1
М	N872
L	N873
XL	N874
XXL	N875

INTEGRA® EC PRODUCT CODE

INTEGRA® PACKAGING				
50	Gloves/Box			
10	Boxes/Case			

INTEGRA®EC PACKAGING			
50	Gloves/Box		
10	Boxes/Case		

GLOVE PROFILE		ASTM D 6319	INTEGRA®	INTEGRA®EC
Length	mm (inches)	min. 220 (8.7)	240 (9.5)	295 (11.6)
Cuff Thickness	mm (mils)	n/a	0.14 (5.5)	0.13 (5.1)
Palm Thickness	mm (mils)	min. 0.05 (2.0)	0.17 (6.7)	0.20 (7.9)
Finger Thickness	mm (mils)	min. 0.05 (2.0)	0.19 (7.5)	0.23 (9.1)
Tensile Strength	Before Aging After Aging	min. 14 min. 14	31 14	23 14
Elasticity/Elongation	Before Aging After Aging	min. 500 min. 400	500 400	500 400
Pinhole Defect Rate*	(AQL)	max. 2.5	1.5	1.5

^{*} Pinhole Defect Rate is FDA minimum requirement.













RECOMMENDED INDUSTRIES

