

Product Data



The “Peak” Series of Hard Hats (A59, A69, A79)



A79



FM44RTV



A59RS1



A79RS2

Product Description:

The Peak series of hard hats has a versatile and dependable design, along with economy and Comfort. This series offers many features and choices to suit different needs. The Peak series comes with a rain trough and accessory slots. It also gives the choice between ratchet or pin-lock adjustments, nylon-web or plastic straps, 4 or 6 points suspensions. The Peak series is ideal for environments where vertical impact on the head is a risk.

Product Number	Description	Order Multiples	Case Quantity	Case Dimensions	Case Weight
A59	Pin-Lock, Plastic suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	8.5 kg. 18.5 lbs.
A59R	Ratchet, Plastic suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	9 kg. 19.5 lbs.
A69	Pin-Lock, Nylon suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	8.5 kg. 18.5 lbs.
A69R	Smooth-Lock ratchet, Nylon suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	9 kg. 19.5 lbs.
A79	Pin-Lock, Nylon suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	8 kg. 17.5 lbs.
A79R	Smooth-Lock ratchet, Nylon suspension	20	20	44.5 X 32 X 62.5 cm. 17.5" X 12.5" X 24.5"	9 kg. 19.5 lbs.

Product Certification:

- **A59, A59R:** Meet the **ANSI Z89.1 – 2003** (USA) standard as **Type I, Class E**; and certified to the **CE EN397 : 1995** (Europe) standard.
- **A69, A69R, A79, A79R:** Meet the **ANSI Z89.1 – 2003** (USA) standard as **Type I, Class E**; and certified to the **CE EN397 : 1995** (Europe) standard and **CSA Z94.1 – 05** (Canada) standard as **Type 1, Class E**.

Product Data



The “Peak” Series of Hard Hats (A59, A69, A79)

Product Characteristics:

A59 & A59R:

Shell Material:	HDPE
Suspension:	4 points of attachment
Suspension Tabs:	HDPE
Suspension Straps:	LDPE
Headband Material:	MDPE
Adjustment Mechanisms:	Acetal
Sweatband Material:	Self-adhesive Polypropylene Foam

A69, A69R, A79 & A79R:

Shell Material:	HDPE
Suspension A69 & A69R:	6 points of attachment
Suspension A79 & A79R:	4 points of attachment
Suspension Tabs:	HDPE
Suspension Assembly:	HDPE
Suspension Straps:	
Material:	Woven Nylon Webbing
Width:	23/32”
Breaking Strength:	300 pounds minimum
Elongation:	19%
Crown Pad Material:	Urethane foam laminated with Vinyl on one side
Sweatband Material:	Closed-Cell Polyethylene foam with Antibacterial Terry-Cloth (Velcro Attachment)
Smooth-Lock Ratchet:	Acetal
Pin-Lock Adjustment:	MDPE

Weight:

A59 & A69:	345 g.
A59R & A69R:	388 g.
A79:	337 g.
A79R:	380 g.

Country of Origin: Made in Canada

Material Declaration:

We declare that the materials and processes used in the manufacturing of this product are not known to cause harmful effect to the wearer. However, it is the users' responsibility to do the proper tests for the specific application.

Disclaimer:

The data, included in this document, incorporates the best information currently available to North Safety Products; and it is derived from sources believed to be reliable. North makes no warranties to the accuracy of the source material.