



CO₂ Fire Extinguisher

Model	SNG01-27	SNG01-28	SNG01-29	SNG01-30	SNG01-31	SNG01-32	SNG01-33	SNG01-34
Type	2kg(A)	2kg(B)	2.3kg(A)	2.3kg(B)	3kg(A)	3kg(B)	4.5kg(A)	4.5kg(B)
Out-diameter(mm)	116	116	116	116	116	116	136	136
Volume(L)	3.0	2.67	3.45	3.1	4.5	4.0	6.75	6
Cylinder Length(mm)	384	350	431	392	540	488	590	533
Cylinder Weight(kg)	3.6	3.69	3.96	4.05	4.79	4.91	7.1	7.5
Working Pressure(Bar)	174	174	174	174	174	174	174	174
Test Pressure(Bar)	250	250	250	250	250	250	250	250
Min Wall-thickness(mm)	2.38	2.58	2.38	2.58	2.38	2.58	2.78	3.01

Model	SNG01-35	SNG01-36	SNG01-37	SNG01-38	SNG01-39	SNG01-40	SNG01-41	SNG01-42
Type	5kg(A)	5kg(B)	6.8kg(A)	6.8kg(B)	7kg(A)	7kg(B)	10kg(A)	10kg(B)
Out-diameter(mm)	136	136	154	154	154	154	154	154
Volume(L)	7.5	6.7	10.2	9.1	10.5	9.35	15	13.4
Cylinder Length(mm)	647	584	680	613	698	630	963	875
Cylinder Weight(kg)	7.66	8.11	10.41	11.02	10.63	11.28	13.96	15.1
Working Pressure(Bar)	174	174	174	174	174	174	174	174
Test Pressure(Bar)	250	250	250	250	250	250	250	250
Min Wall-thickness(mm)	2.78	3.01	3.14	3.40	3.14	3.4	3.14	3.40

Model (A) filling ratio k=0.67 Model (B) filling ratio k=0.75 Temperature Range:-30°C ~ +60°C