



Product Family










## Miller Falcon Self-Retracting Lifelines

Pound for pound the strongest, most durable retractable. Lifeline available in 16-ft., 20-ft., 30-ft., 50-ft. and 65-ft. lengths.

[Visit MillerFallProtection.com](http://MillerFallProtection.com) >  
[Interactive Miller Catalog](#) >  
[Access the Miller Photo Gallery](#) >



Product Numbers & Ordering Information	Product Numbers	Details
	MP16P/16FT	<b>Web Lifeline; ANSI A10.32 Compliant</b> 16-ft. [4.9m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity
	MP16P-Z7/16FT	<b>Web Lifeline; ANSI Z359-2007 Compliant</b> 16-ft. [4.9m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity
	MP20G/20FT	<b>Cable Lifeline; ANSI A10.32 Compliant</b> 20-ft. [6.1m] galvanized wire rope (3/16"); tagline and carabiner

	<p><b>MP20G-Z7/20FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                  20-ft. [6.1m] galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP20P/20FT</b></p>	<p><b>Web Lifeline; ANSI A10.32 Compliant</b>                  20-ft [6.1m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity</p>
	<p><b>MP20P-Z7/20FT</b></p>	<p><b>Web Lifeline; ANSI Z359-2007 Compliant</b>                  20-ft [6.1m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity</p>
	<p><b>MP20SS/20FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                  20-ft [6.1m]; stainless steel wire rope (3/16") with tagline and carabiner</p>
	<p><b>MP20SS-S/20FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                  20-ft [6.1m] stainless steel wire rope (3/16"); stainless steel snap hook; tagline and carabiner</p>
	<p><b>MP30G/30FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                  30-ft [10m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP30G-Z7/30FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                  30-ft [10m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP30SS/30FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                  30-ft [10m]; stainless steel wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP30SS-S/30FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                  30-ft. [10m]; stainless steel wire rope (3/16"); stainless steel snap hook; tagline and carabiner</p>

	<p><b>MP30SS-Z7/30FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                      30-ft [10m]; stainless steel wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP50G/50FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                      50-ft [15m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP50G-Z7/50FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                      50-ft [15m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP50SS/50FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                      50-ft. [15m]; stainless steel wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP50SS-Z7/50FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                      50-ft. [15m]; stainless steel wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP65G/65FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                      65-ft [20m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP65G-Z7/65FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                      65-ft [20m]; galvanized wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP65SS/65FT</b></p>	<p><b>Cable Lifeline; ANSI A10.32 Compliant</b>                      65-ft. [20m]; stainless steel wire rope (3/16"); tagline and carabiner</p>
	<p><b>MP65SS-Z7/65FT</b></p>	<p><b>Cable Lifeline; ANSI Z359-2007 Compliant</b>                      65-ft. [20m]; stainless steel wire rope (3/16"); tagline and carabiner</p>



**Overview**

**Key Features**

- Corrosion-resistant stainless steel and aluminum internal components extend service life and reduce replacement costs
- Lightest composite unit on the market – easy to handle and transport to/from jobsites
- Unique side payout design reduces wear on the entry guide bushing and cable for smooth operation with less drag
- Smooth, quiet operation; engineered spring retraction tension designed not to pull or drag on a worker to improve productivity and reduce fatigue
- Built-in, ergonomically-designed molded handle on the 50-ft (15m) and 65-ft. (20m) cable units provide support and leverage when attaching C3811 anchorage connector. Easier to install. Dual swivels D3814 (unit top and snap hook) included on all cable models to minimize lifeline from twisting during use

**Recommended Industries/Use**

- Construction
- Steel and Metals
- Transportation

**Hazards**

- Confined Space
- Fall from height

**Regulations**

- - Meets all applicable OSHA, ANSI and CSA standards

**Warranty Information**

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

**Specifications**

<b>Falcon Cable Maximum Working Load</b>	Rated to 400 lbs. (181.4kg) capacity when using a SofStop shock absorber (928LS/18INYL)
<b>Falcon Web Maximum Working Load</b>	Rated for up to 400 lbs. (181.4kg) worker
<b>Load indicators</b>	Cable models – on snap hook Web models – flag on

## Miller Falcon SRLs

<b>(identifying when the unit needs to be removed from service)</b>	webbing
<b>Housing</b>	High impact-resistant nylon
<b>Specification Sheets</b>	For full engineering specification sheets, go to the spec sheet section under downloads and documentation

### Literature & Documents

#### Miller Falcon Brochure

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fa-Retracting\\_Lifelines/20606/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fa-Retracting_Lifelines/20606/1033.aspx)

Learn more about the Miller Falcon

#### Miller SRL Manual

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fa-Retracting\\_Lifelines/15824/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fa-Retracting_Lifelines/15824/1033.aspx)

Miller Self-Retracting Lifeline Instruction Manual

#### Falcon Web Spec Sheet

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fa-Retracting\\_Lifelines/16183/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fa-Retracting_Lifelines/16183/1033.aspx)

SP345 Falcon Web Spec Sheet

### Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

### Additional Information

800/873-5242 or 814/423-2118 email: [millertecheexpert@sperianprotection.com](mailto:millertecheexpert@sperianprotection.com)

### Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: [millertecheexpert@sperianprotection.com](mailto:millertecheexpert@sperianprotection.com)



For general inquiries  
800.343.3411

[View other region sites](#)

© 2011 Honeywell International Inc.