# **Lightweight/Comfort Harnesses**

## **Description**

A complete line of lightweight, comfort welder harnesses features blue, flame-retardant Nomex® webbing to protect against weld splatter. The special inner Kevlar® core adds strength and high-temperature resistance.

### **Materials**

Webbing: 1-3/4" Kevlar®/Nomex®

Elastic Keepers: Elastic

Thread (Stitching): Kevlar, Polyester

\*D-Ring: Clear Chromate Finished Carbon Steel
\*Buckles: Clear Chromate Finished Carbon Steel

Labels: Valeron

Back D-ring Pad: Evoprene, Leather Label Pack: Evoprene, Nylon

#### Technical.

 Max. Working Load:
 400lbs (181.4kg)

 Webbing Min.Tensile:
 5000lbs (22kN)

 D-ring Min. Tensile:
 5000lbs (22kN)

 Buckle Min. Tensile:
 4000lbs (18kN)

## **Certification**

Meets OSHA 1926.502, ANSI A10.32, Z359.1 and CSA requirements.

	<b>Q</b> 4	
Y		

Model No.	Shoulder Strap	Chest Strap	Leg Straps	Front D-ring	Side D-rings	Special Features
650K/UBL	Friction	Mating Buckle	Mating Buckle	Option	No	Belt loops/ pull-up adjustment
650K-7/UBL	Friction	Mating Buckle	Mating Buckle	Option	Yes	Belt loops/pull-up adjustment
650K-25/UBL	Friction	Mating Buckle	Mating Buckle	Option	Yes	Shoulder D-rings/Belt loops/pull-up adjustment
751K/UBL		Mating Buckle	Mating Buckle	Option	No	
850K/UBL	Friction	Mating Buckle	Mating Buckle	Option	No	Pull-down adjustment
850K-3/UBL	Friction	Mating Buckle	Mating Buckle	Option	No	Shoulder D-rings/Pull-down adjustment
850K-4/UBL	Friction	Mating Buckle	Tongue Buckle	Option	No	Pull-down adjustment
850K-7/UBL	Friction	Mating Buckle	Mating Buckle	Option	Yes	Pull-down adjustment

Model numbers listed are for <u>universal size</u>. Harnesses are also available in small/medium and XXIarge by replacing the "U" in the model number with "S/M" or "XXL". All listed models include a back D-ring and sub-pelvic strap.



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

<sup>\*</sup> All hardware meets ASTM (50) fifty-hour salt spray test requirements.