

LEIGHTNING L2F FOLDING HI-VISIBILITY

PRODUCT INFORMATION

When the jobsite is outdoors or in low lighting, workers are exposed to increased safety hazards in addition to noise.

Leightning Hi-Visibility earmuffs provide workers with a total solution for both hearing protection and visibility at night - and during the day. Its eye-catching fluorescent green earcups provide a highly noticeable contrast against dark settings, especially in low lighting situations and inclement weather. Plus, Leightning Hi-Visibility are the only earmuffs that incorporate an exclusive reflective headband that illuminates when exposed to light, providing increased visibility and safety on the job.

PRODUCT FEATURES

- Fluorescent Green Earcups provides additional \Rightarrow high visibility and contrast on the job.
- Ideal to wear at night, during the day, in low \Rightarrow light, and under inclement weather conditions.
- Bright fluorescent green color does not fade \Rightarrow when exposed to sunlight.
- **Reflective Padded Foam Headband illuminates** \Rightarrow under light for increased visibility and safety, especially in low lighting. It delivers longwearing comfort and has minimal headband pressure on the head.
- Air Flow Control[™] Technology for better, \Rightarrow consistent attenuation, especially at low frequencies.
- Steel Wire Construction, robust design \Rightarrow withstands demanding use, especially in tough environments
- Snap-In Ear Cushions makes cushion \Rightarrow replacement quick and easy.
- Telescoping Height Adjustment with individual \Rightarrow setting for personalized comfort. Remains fixed during usage
- Convenient folding design for easy storage. \Rightarrow
- Belt storage case available separately. \Rightarrow

APPLICATIONS

Noise environments between 105dB to less \Rightarrow than 110dB(A).

ORDERING INFORMATION



TECHNICAL INFORMATION

Materials:	Headband - Steel Wire, PUR-E, PVC, Textile Cup - ABS
	Ear Cushion - PVC/PUR-E (Polyurethane)
Hygiene Kit:	Part # 1011999
Headband force:	10N
Weight:	236g

STANDARDS

 \Rightarrow

- Approved to AS/NZS 1270:2002 \Rightarrow License number 1133
 - SLC₈₀ 30dB Class 5

Frequency	125	250	500	1000	2000	4000	8000
Mean Value dB	20.8	24.6	30.0	31.6	32.0	38.9	39.4
Std Deviation dB	2.9	2.3	2.9	2.9	2.4	2.6	2.9
Mean-Std Dev dB	17.9	22.3	27.1	28.7	29.6	36.3	36.5

Part Number	Description	Pairs Per Box	Min order (box)		Case Dimensions L x W x H (mm)	Case Weight	Bar code
1013942	Leightning L2F Folding High Visibility	1	20	288g	290 x 280 x 290	6.62kg	033552014461

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PRO-TECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Sperian Protection Australia Pty Ltd Ph Aust: 1300 139 166 NZ: 0800 322 200 www.sperianprotection.com.au