Miller Oil Rig "Belly Buster" Harness

Description

The Miller Oil Rig "Belly Buster" Harness features a permanently-attached waist belt and an 8-inch (203 mm) abdomen pad designed for "hands-free" positioning while working on oil rig platforms (monkey boards). Additionally, a riding harness (saddle seat) for raising and lowering workers is also available.

Materials

Webbing: 1-3/4" Polyester

Elastic Keepers: Elastic

Thread: 6 cord bonded 3 strand polyester thread

Locking Carabiner: Steel, Aluminum

Belly Buster Pad

- External: Synthetic leather (Millerhyde™)
- Internal: 8-in. (203mm) wide polyester pad
1-3/4" polyester reinforcement straps

Saddle Seat: 3-in. (76mm) Polyester

Back D-ring Pad: Copolymer Polypropylene, Evoprene

Label Pack: Evoprene, Nylon

Label Materials: Valeron

D-Ring* Clear Chromate Finished Carbon Steel
Buckles* Clear Chromate Finished Carbon Steel

Grommets* Brass

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load: 400 lbs (181.4kg)

Minimum Tensile

- D-Ring 5000 lbs. (22kN) - Buckles 4000 lbs. (18kN) - Thread: 42 lbs. (0.19kN) - Webbing: 5000 lbs. (22kN)

Certification

Meets applicable ANSI A10.32, Z359.1; OSHA 1910.66, 1926.502(d) requirements

Model	Description
850-OIL/LYL	"Belly Buster" harness with permanently-attached belt; rigid 8-in. (203mm) abdomen pad; built-in auto-locking carabiners; tongue buckle leg straps.
850DT-OIL-RS/LAG	Combination "Belly Buster" harness with permanently-attached belt; rigid 8-in. (203mm) abdomen pad; built-in auto-locking carabiners; tongue buckle leg straps; built-in saddle seat with D-rings and aluminum carabiner for raising/lowering.
080230/LGN	Combination "Belly Buster" harness with permanently attached belt (with 4-hole pad), rigid 8-in. (203mm) abdomen pad; built-in auto-locking carabiners; built-in saddle seat with D-rings and aluminum carabiner for raising/lowering.



