

**New!**

# Miller® Contractor Harness

*Specifically designed for use in construction*


- Lightweight for greater comfort; non-stretch webbing
- Unique combination back D-ring pad/ shoulder pads that minimize discomfort/stress around the neck and shoulders when using a tool belt
- Soft lumbar back pad for additional support and comfort
- Waist belt (removable) to accommodate tool pouches
- Single, back D-ring for fall protection
- Tongue buckle leg straps for easy adjustment
- Friction buckle shoulder adjustments; mating buckle chest adjustment
- Self-contained label pack positioned for easy access
- Two (2) pull-free lanyard rings
- Rated to 400 lbs. (181.4 kg) capacity
- Meets applicable OSHA, ANSI and CSA Standards



Tongue buckle leg straps



Self-contained label pack



Two (2) pull-free lanyard rings

SKU	Size	Back D-Ring	Front D-Ring	Side D-Rings	Chest Strap Buckle	Shoulder Strap Buckles	Leg Strap Buckles	Sub-Pelvic Strap	Special Features
650CN-BP/UGN	Universal (L, XL)	Yes	Option	No	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops
650CN-BP/S/MGN	Small/Medium	Yes	Option	No	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops
650CN-BP/XXLGN	XXL	Yes	Option	No	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops
650CN-BDP/UGN	Universal (L, XL)	Yes	Option	Yes	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops
650CN-BDP/S/MGN	Small/Medium	Yes	Option	Yes	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops
650CN-BDP/XXLGN	XXL	Yes	Option	Yes	Mating	Friction	Tongue	Yes	D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops

*This equipment should only be used in conjunction with the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.*



▶ Ask the Expert ... Ask Miller.

800/873-5242  
or 814/432-2118

Fax 800/892-4078  
or Fax 814/432-2415

www.millerfallprotection.com



For more information or to place an order, please contact your Miller® distributor:

LMCH/0308/15M/RPI