

**New!**

# Miller® Vinyl-Coated Fall Protection Products

*Designed for "Dirty Job" Environments*

A new line of **Miller Revolution™ Harnesses** and **Miller® Shock-Absorbing Lanyards** features a special vinyl coating on the webbing to protect against a variety of liquids that could compromise overall performance. Miller Vinyl-Coated Products are effective in a wide range of applications, including:

- Food Processing**
- Petrochemical**
- Water Treatment**
- Painting**
- Billboards**
- General Industry**



Vinyl-coated webbing prevents absorption of liquids and is easy to clean.



#RPC-TB/UGN

## Miller Revolution™ Harnesses

- The unique rotary PivotLink™ connection design that provides greater comfort in bending/mobility
- Tongue buckle leg straps for easy donning and adjustment
- Two (2) pull-free lanyard rings
- Clip-on design web finials organize webbing after proper adjustment
- Integrated, self-contained label pack that safely encapsulates labels, minimizing damage and loss
- User-rated to 400 lbs (181.4kg)



PivotLink connection



Self-contained label pack



Two (2) pull-free lanyard rings

Ask the Expert ...  
Ask Miller.

Miller Technical Service  
**800/873-5242**  
www.millerfallprotection.com

SKU	Size	Back D-Ring	Front D-Ring	Side D-Rings	Chest Strap Buckle	Shoulder Strap Buckles	Leg Strap Buckles	Sub-Pelvic Strap	Special Features
RPC-TB/UGN	Universal	Yes	Option	No	Mating	Friction	Tongue	Yes	—
RPC-TB-BD/UGN	Universal	Yes	Option	Yes	Mating	Friction	Tongue	Yes	Removable belt with side D-rings

# Miller Vinyl-Coated Shock-Absorbing Lanyards



- SofStop® shock absorber pack is designed with a specially-woven inner core that smoothly expands up to 42 (1.1m) inches to safely reduce fall arrest forces
- Heavy-duty back-up safety strap
- Zinc-plated steel snap hooks
- User-rated to 310 lbs. (140.6kg)

#913PC/6FTGN



#922PCR/6FTGN



#8798PC/6FTGN



#87987PCR/6FTGN



Miller Vinyl-Coated Fall Protection Products meet all applicable OSHA, ANSI Z359-2007 and CSA Standards.

SKU	Material	Style	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
913PC/6FTGN	Vinyl-coated webbing	SofStop Lanyard	One	Locking snap hook	Locking snap hook	6' (1.8m)
922PCR/6FTGN	Vinyl-coated webbing	SofStop Lanyard	One	Locking snap hook	Locking rebar hook	6' (1.8m)
8798PC/6FTGN	Vinyl-coated webbing	SofStop Lanyard	Two	Locking snap hook	Locking snap hooks	6' (1.8m)
87987PCR/6FTGN	Vinyl-coated webbing	SofStop Lanyard	Two	Locking snap hook	Locking rebar hooks	6' (1.8m)

*This equipment should only be used in conjunction with the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.*



▶ Ask the Expert ... Ask Miller.

800/873-5242  
or 814/432-2118

Fax 800/892-4078  
or Fax 814/432-2415

www.millerfallprotection.com



For more information or to place an order, please contact your Miller® distributor:

LMVCP/0308/20M/RPI