





Product Family

Titan T-Bak Lanyard

The T-BAK lanyard with pack-type shock absorber is designed for tie-back use, eliminating the need for a separate anchorage connector.

[Visit MillerFallProtection.com >](http://MillerFallProtection.com)
[Interactive Miller Catalog >](#)
[Access the Miller Photo Gallery >](#)



Product Numbers & Ordering Information	Product Numbers	Details
	T6111TB/3FTAF	Web Lanyard with Tie-Back Use 3-ft single leg; locking snap hook for harness connection; sliding D-ring; auto-lock carabiner at anchor end
	T6111TB/6FTAF	Web Lanyard with Tie-Back Use 6-ft single leg; locking snap hook for harness connection; adjustable D-ring; twist-lock carabiner at anchor end
	T6121TB/4FTAF	Web Lanyard with Tie-Back Use 4-ft double leg; locking snap hook for harness connection; (2) adjustable D-rings, (2) twist lock carabiner at anchor end and shock absorber pack
	T6121TB/6FTAF	Web Lanyard with Tie-Back Use 6-ft double leg; locking snap hook for harness connection; (2) adjustable D-rings, (2) twist lock carabiner at anchor end and shock absorber pack

	<p>T6121TBDP/6FTAF</p>	<p>Web Lanyard with Tie-Back Use 6-ft double leg; locking snap hook for harness connection; (2) adjustable D-rings, (2) twist lock carabiner at anchor end and double-pack shock absorber</p>
	<p>T6121TB-Z7/6FTAF</p>	<p>Web Lanyard with Tie-Back Use ANSI Z359-2007 Compliant 6-ft double leg; locking snap hook for harness connection; (2) adjustable D-rings, (2) twist lock carabiner at anchor end and shock absorber pack</p>

Overview

Key Features

- Special webbing (9800 lbs. [4445kg]) for greater abrasion resistance
- Forged sliding D-ring for ease of use
- Auto-locking carabiner for added safety
- Locking snap hook for connecting to the harness back D-ring
- Shock-absorber pack that keeps fall forces at or below 900 lbs. (408kg)

Hazards

- Confined Space
- Fall from height

Regulations

- - Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

<p>Specification Sheets</p>	<p>For full engineering specification sheets, go to the spec sheet section under downloads and documentation</p>
------------------------------------	--

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com



For general inquiries
800.343.3411

View other Sperian Sites
© 2011 Sperian Protection