







**Product Family**

## Titan Self-Retracting Lifelines

Titan Self-Retracting Lifelines are ideal for a full-range of applications including construction and general maintenance.

[Visit MillerFallProtection.com >](http://MillerFallProtection.com)  
[Interactive Miller Catalog >](#)  
[Access the Miller Photo Gallery >](#)



Product Numbers & Ordering Information	Product Numbers	Details
	TR20/20FT	<b>Titan Cable Self-Retracting Lifeline</b> 20-ft. Galvanized Wire Rope [3/16"]; Composite housing.
	TR30/30FT	<b>Titan Cable Self-Retracting Lifeline</b> 30-ft. Galvanized Wire Rope [3/16"]; Composite housing.
	TR50/50FT	<b>Titan Cable Self-Retracting Lifeline</b> 50-ft. Galvanized Wire Rope [3/16"]; Composite housing.
	TR65/65FT	<b>Titan Cable Self-Retracting Lifeline</b> 65-ft. Galvanized Wire Rope [3/16"]; Composite housing.

Overview

**Key Features**

- Affordably priced
- Quick-activating braking mechanism
- Variety of working lengths
- Quick-activating stainless steel braking mechanism arrests free falls
- No annual factory recertification required\*
- Snap hook with swivel; carabiner included
- Narrow payout port

**Hazards**

- Confined Space
- Fall from height

**Regulations**

- - Meets all applicable OSHA, ANSI and CSA standards

**Warranty Information**

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

**Specification Sheets**

For full engineering specification sheets, go to the spec sheet section under downloads and documentation

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

**Additional Information**

800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

**Technical Support**

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com



For general inquiries  
800.343.3411

View other Sperian Sites  
© 2011 Sperian Protection