Regulators

FLOW GAUGE / FLOW METER

SR 310, SR 311, & SR 312

Flow Meter

DESIGN/CONSTRUCTION

- Designed for CO₂ application (non-siphoned tube cylinders)
- High flow CO₂ applications (SR 310 100 psig) (SR 311/312 100 SCFH) with adequate supply or source
- Designed for core wire applications
- · Machined aluminum body & housing cap
- 2" (50.8 mm) gauge
- Stem type seat mechanism
- 1.75" (44.5 mm) diaphragm fabric reinforced neoprene
- Self reseating relief valve (not designed to protect downstream equipment)
- · Sintered inlet filter bronze

DIMENSIONS

8.38" W x 7.25" H x 2.5" D (212.9 mm x 184.2 mm x 63.5 mm)


WEIGHT

2 lb 15 oz (1.33 kg)

PERFORMANCE

- Maximum inlet 1500 psig
- Delivery range 100 SCFH

A regulator equipped with a flow gauge is not accurate when a back pressure in excess of 2 psig exists at the outlet. Back pressure is caused by a restriction in the equipment downstream of the flow gauge. Metering valves, kinked hoses or even very long hoses are restrictions that can cause back pressure. In applications where back pressure in excess of 2 psig can be expected, a regulator equipped with a flow meter should be used.



Gas Service	Part No.	Model No.	Flow Range	CGA Inlet Connection
Carbon Dioxide	0781-0355	SR 310 Adjustable Pressure Gauge	10-200 psig	320
	0781-0353	SR 311 (Preset @ 80 psig) Flow Meter	25-100 SCFH	320
	0781-0354	SR 312 Flow Gauge	0-100 SCFH	320

Outlet Connections: 5/8"-18 RH(F)
Adapter: 5/8"-18(M) x 1/4" NPT(M) (Part No. 0950-0163)





GAS HEATER

Manufactured for either Carbon Dioxide (CO₂) or Nitrous Oxide (N₂O). These heaters operate on 110 Volts at 120 Watts (1 Amp). They are thermostatically controlled at $160^{\circ}F$ (+5°) and rated for flows up to 160 SCFH. Rated for standard cylinder pressures up to 3000 psi.



